

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/010871 A1

(51) International Patent Classification⁷: **G11B 7/00**

(21) International Application Number:
PCT/AU2004/000987

(22) International Filing Date: 23 July 2004 (23.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003903802 23 July 2003 (23.07.2003) AU

(71) Applicant (for all designated States except US): **BAND-
WIDTH FOUNDRY PTY LTD [AU/AU]**; 102 National
Innovation Centre, Australian Technology Park, Eveleigh,
New South Wales 1430 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BURYAK, Alexan-
der [AU/AU]**; 53 Coronga Crescent, Killara, New South
Wales 2071 (AU). **KOLOSSOVSKI, Kazimir [RU/AU]**;

72 Lachlan Street, Macquarie, Australian Capital Terri-
tory 2614 (AU). **STEPANOV, Dmitrii, Yu [RU/AU]**; 7/126
Croydon Avenue, Croydon Park, New South Wales, 2133
(AU).


(74) Agent: **FREEHILLS CARTER SMITH BEADLE**;
Level 32, MLC Centre, 19-29 Martin Place, Sydney, New
South Wales 2000 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: **OPTICAL DATA CARRIER SYSTEM**



(57) Abstract: The present invention provides a method of holographically storing data as in a series of grating structures including m -level coded elements in an optical data carrier, wherein $m \geq 2$, the method comprising: forming a grating sampling function as a direct sum of N partial grating sampling functions, each partial grating sampling function having a phase (ϕ_n) and amplitude (d_n), wherein each d_n has m possible values.

WO 2005/010871 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- with international search report